

★ Jockey EN Series

Jockey Pump Fire Pump Control Panels operates the system according to EN12845.

- ◇ Factory equipped with Isolating switch with door locking system
- ◇ Different types of connections to start and stop motor such as; pressure switches/sensors,



Technical Features

- Metal Enclosure / IP 54
- Main switch with locking mechanism
- Green LED for Motor Running / Red LED for failures
- Power supply 3-50/60Hz 400V ±%15
- Input for Start Command
- Alarms and signals;
 - Motor Overcurrent (Adjustable)
 - Motor low current (Adjustable)
 - Phase Loss failure (Adjustable)
 - Phase Sequence failure (Adjustable)
 - Min / max voltage (Adjustable)
 - Motor starting time
- Adjustable weekly test run
- Alarm outputs (NC-5A/250V)

Technical Data

Jockey EN Control Panel

Jockey EN	COD	VOLTAGE	MAX		CURRENT		BOX DIMENSIONS			WEIGHT	
		V-	kW	Hp	Range (A)	Max (A)	H	L	W	Materials	KG
Jockey/EN - 0.55	25401	3 - 400	0.55	0.75	1.7-2.3	2.3	400	300	175	Metallic	
Jockey/EN - 0.75	25402	3 - 400	0.75	1	3.1-4.2	4.2	400	300	175	Metallic	
Jockey/EN - 1.1	25403	3 - 400	1.1	1.5	3.1-4.2	4.2	400	300	175	Metallic	
Jockey/EN - 1.5	25404	3 - 400	1.5	2	5.7-7.6	7.6	400	300	175	Metallic	
Jockey/EN - 2.2	25405	3 - 400	2.2	3	7.6-9	9	400	300	175	Metallic	
Jockey/EN - 3	25406	3 - 400	3	4	10-12	12	400	300	175	Metallic	
Jockey/EN - 4	25407	3 - 400	4	5.5	10-12	12	400	300	175	Metallic	
Jockey/EN - 5.5	25408	3 - 400	5.5	7.5	13-16	16	400	300	175	Metallic	
Jockey/EN - 7.5	25409	3 - 400	7.5	10	16-20	20	400	300	175	Metallic	
Jockey/EN - 9.2	25410	3 - 400	9.2	12.5	20-24	24	400	300	175	Metallic	
Jockey/EN - 11	25411	3 - 400	11	15	29-32	32	400	300	175	Metallic	
Jockey/EN - 15	25412	3 - 400	15	20	35-38	38	400	300	175	Metallic	

*It is possible to realize the panel for 18.5 kW and largest capacity according to demand

**Please contact us for custom design production

Optional Accessories

Pressure Transmitter



Model	Power (V)	Range Settings
P-T/10	12	10 Bar
P-T/16	12	16 Bar
P-T/25	12	25 Bar
P-T/40	12	40 Bar

Pressure Switch



Model	Range	Range Settings
P-S/10	1-5 Bar	10 Bar
P-S/16	3-12 Bar	16 Bar
P-S/25	2-14 Bar	25 Bar