

★ Smart Jockey EN Series

Jockey Pump Fire Pump Control Panels with smart user interface operates the system according to EN12845.

- ◇ Easy and quick set-up features with navigation buttons and readable LCD display
- ◇ Factory equipped with Isolating switch with door locking system
- ◇ Different types of connections to start and stop motor such as; pressure switches/sensors, etc.



Technical Features

- Metal Enclosure / IP 54
- Main switch with locking mechanism
- 128 x 64 LCD Graphical Display
- Green LED for Motor Running / Red LED for failures
- Power supply 3-50/60Hz 400V \pm 15%
- Input for Start Command
- Alarms and signals;
 - Motor Overcurrent (Adjustable)
 - Motor low current (Adjustable)
 - Phase Loss failure (Adjustable)
 - Phase Sequence failure (Adjustable)
 - Min / max voltage (Adjustable)
 - Motor starting time
- MODBus (RS485)
- Password protection for un-authorized people access.
- USB port for downloading failures, messages, events and alarms with date&time. (Last 500)
- Adjustable weekly test run
- Maintenance time displays and messages
- Alarm outputs (NC-5A/250V)

Technical Data

Smart Jockey EN Control Panel

Smart Jockey EN	COD	VOLTAGE	MAX		CURRENT		BOX DIMENSIONS				WEIGHT
		V-	kW	Hp	Range (A)	Max (A)	H	L	W	Materials	KG
Smart Jockey/EN-4	25301	3 - 400	4	5.5	7.6-9	9	400	300	175	Metallic	
Smart Jockey/EN-5.5	25302	3 - 400	5.5	7.5	10-12	12	400	300	175	Metallic	
Smart Jockey/EN-7.5	25303	3 - 400	7.5	10	2.6-16	16	400	300	175	Metallic	
Smart Jockey/EN-11	25304	3 - 400	11	15	16-25	25	400	300	175	Metallic	
Smart Jockey/EN-15	25305	3 - 400	15	20	16-32	32	400	300	175	Metallic	

**It is possible to realize the panel for 18.5 kW and largest capacity according to demand*

***Please contact us for custom design production*

Optional Accessories

Pressure Transmitter



Model	Power (V)	Range Settings
P-T/10	12	10 Bar
P-T/16	12	16 Bar
P-T/25	12	25 Bar
P-T/40	12	40 Bar

Pressure Switch



Model	Range	Range Settings
P-S/10	1-5 Bar	10 Bar
P-S/16	3-12 Bar	16 Bar
P-S/25	2-14 Bar	25 Bar